





THANK YOU FOR PURCHASING A FINE U.S. MADE TOOL
FROM THE PEOPLE WHO PIONEERED THE FIRST PRACTICAL BX CUTTER
THE MIGHTY-MITER CONSISTS OF AN ADJUSTABLE VISE THAT SECURES THE MATERIAL TO BE CUT WITH AN
ADJUSTABLE QUICK CLAMPING SYSTEM. THE VISE & CLAMPING ASSEMBLY SWINGS UP TOWARDS THE
RECIPROCATING BLADE WHICH CUTS VIRTUALLY ANYTHING PERFECTLY SQUARE.



**MADE IN
U.S.A**



WARNING!! Always unplug the reciprocating saw line cord before installing the Mighty-Miter

STEP 1 - RECIPROCATING SAW SHOE REMOVAL AND ASSEMBLY

STANDARD SAWZALL® - Remove the four screws with a 5/32" wrench on each side of the Sawzall®. Slide out the shoe from the tool. Slide the Mighty-Miter® all the way into place and retighten the four screws on the Sawzall®.

SUPER SAWZALL® - Simply lower the lever that adjusts the depth of the shoe, and remove the Super Sawzall® boot. Insert the Mighty-Miter all the way into the mounting hole and lock the lever.

18V SAWZALL® - Simply untighten the set screw with a 5/32" hex wrench and remove the shoe. Insert the Mighty-Miter accessory all the way into the mounting hole and retighten the set screw securely to prevent any motion.

DeWalt® DW-303 - Hold saw vertically on a table. Place nut plate just below the top shoe (between shoe and side shield) and line up with lower 2 holes. Mighty-Miter® has two locating pins, place these into the top 2 holes on the DeWalt® shoe. Screw in 2 cap screws using 3/16" Allen wrench.

Make sure that the blade is parallel to the reciprocating saw. If not, bend or twist the blade to ensure a square cut. (Always Wear Safety Goggles)

STEP 2 - MIGHTY-MITER HANDLE ASSEMBLY

The Mighty-Miter handle may be assembled on either the right or left side. Simply unscrew the two screws from the adapter and screw the handle on the preferred side using a 1/8" Allen wrench.

STEP 3 - CABLE CLAMPING

The Mighty-Miter has a quick clamping feature, simply unscrew the thumbscrew ① with the red cap one full turn. This allows the clamping jaw ② to quickly travel the full range. Place the material to be cut in the jaw ③ and lower the clamping jaw ①. Retighten the quick clamping screw ②. Check that the material sits squarely in the jaw and the handle ③. Now tighten the plastic knob ④ to clamp the material securely. Small adjustments can be made with this knob ④, however it is convenient to use the quick clamping screw ① when making large adjustments.

WARNING!! Never attempt to cut already installed BX, MC or Flex cables on live lines, since any contact between a live wire and ground can be lethal.

STEP 4 - CUTTING WITH THE MIGHTY-MITER (RANGE 1/8" TO 2" DIA.)

After the material has been clamped, hold the Sawzall® handle with your right hand, while grabbing the Mighty-Miter handle ③ with your left. Start the Sawzall® and slowly rotate the Mighty-Miter towards the blade. Continue applying pressure until the material is cut completely through. Stop the Sawzall® and removed the finished piece and unclamp the Sawzall® from the part. Note that it is possible to use the Mighty-Miter in place on the floor or tabletop when cutting long materials by simply pushing down on top of the Mighty-Miter, the jaw will rotate to cut the material automatically.

STEP 5 - REINSTALLING SAWZALL® SHOE

To return the Sawzall® to normal use follow the Instructions in Step 1 in reverse to reinstall the shoe.

All brands and product names are trademarks or registered trademarks of their respective companies

BLADE REPLACEMENT

Refer to the instructions included with your Sawzall® to change the blade. When replacing a blade make sure that the blade is parallel to the center line of the Sawzall® in order to get a square cut.

WARRANTY















All the **Mighty-Miter** models have a **3 month guaranty** except for the blade. They are warranted to be free from defects in workmanship and material. Should any part of these tools be defective, they will be serviced or replaced free of charge (except for replacement blade).

This warranty is void if these tools have been damaged by accident or mishandling. **THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES EXPRESS OR IMPLIED**, except for repair or replacement of parts, Seatek Company assumes no liability for damage to the replacement blade or other damages.



CUT ANY OF THESE SHAPES PLUS MANY MORE!

ACCESSORIES & TOOLS

<p>REPLACEMENT BLADES</p> 	<p>B-102 B-107 B-108</p>	<p>BLUE SAPPHIRE BLADE FOR ALL ABOVE TOOLS. RS-101, RS-101A, RF-120A, RF-120B & RF-170. SAME AS ABOVE BUT FOR ALUMINUM (WORKS ON STEEL CASING TOO BUT ONLY FOR 1/2" TRADE SIZE & ABOVE). FOR ALL POWER TOOLS & MACHINES RS-101-AP, PC-205A, RM-202A, B & C, RM-202M AND RSK-155A.</p>		<p>101-110</p>	<p>HANDLE ASSEMBLY FOR RS-101, RS-101A, RF120A, RF-120B AND RF-170 WITH BLADE CARTRIDGE STORED IN KNOB.</p>
<p>LUBRICANT</p> 	<p>LS-105</p>	<p>LUBRICANT STICK FOR BLADES AND RS-101, RS-101A, RS-101AP, RF120A, RF-120B & RF-170 AND ALL ROTOMATIC MODELS.</p>	<p>"SUPER-BELT" <i>Electrician's Tool Belt</i></p> 	<p>NEW! PL-2000</p>	<p>EXCLUSIVE WEIGHT LIFTING STYLE TOOL BELT WITH A PROFESSIONAL TOOL CADDY & AN EASY TO REACH, HIP POCKET STYLE. GUARANTEES THE BEST WEIGHT DISTRIBUTION OF YOUR TOOLS AROUND YOUR BODY. GENUINE LEATHER CONSTRUCTION. 15 TOOL HOLDERS, ELECTRICAL TAPE HOLDER WITH A QUICK RELEASE GRIP.</p>
<p>LEATHER HOLDER</p> 	<p>LP-103</p>	<p>LEATHER TOOL HOLDER FOR RS-101, RS-101A, RS-101AP ZS-140, RF-170, & SW-130</p>	<p>STRIP-ALL</p> 	<p>SA-200</p>	<p>STRIPPER FOR JACKETED CABLES (PLASTIC, TEFLON OR RUBBER). STRAIGHT & RING CUTTING FROM 1/4" TO 5/8" DIA. WITH WIRE STRIPPER, FOLDING KNIFE BLADE & REPLACEMENT BLADE. PRECISION DEPTH OF CUT ADJUSTMENT.</p>
<p>HARDWARE RETROFIT</p> 	<p>101-106</p>	<p>SPARE PART KIT FOR RS-101, RS-101A, RF120A, RF-120B & RF-170. CONSISTING OF ONE SHAFT, ONE NUT, ONE 4-40 KNURLED SCREW, ONE THUMBSCREW FOR RS-101 ONLY.</p>	<p>SWING-SAW</p> 	<p>SW-130</p>	<p>COMPACT HAND TOOL TO CUT SQUARE ANY LIQUID TIGHT CONDUIT. CAN BE USED ON PLASTIC, COPPER, ALUMINUM & STEEL TUBING, THREADED RODS, EMT CONDUIT, SURFACE RACEWAYS ETC. MAXIMUM VISE JAW OPENING 1-1/2". BLADES ARE EASILY REPLACED.</p>
<p>POWER KIT</p> 	<p>101-107</p>	<p>POWER CONVERSION KIT. MOTORIZE ANY ROTO-SPLIT AND ROTO-FLEX (SAME PRINCIPLE AS POWER-SPLIT). CONSISTS OF B-108 BLADE, SHAFT, SCREW, WASHERS, HEX NUT & HEX WRENCH.</p>	<p>"HINGENIOUS"</p> 	<p>FT-210</p>	<p>CAM ACTION, HINGED FISH TAPE PULLER, TWO HANDED ACTION FOR TWICE THE PULLING FORCE. MUCH SAFER AND PREVENTS KINKS IN TAPE.</p>
<p>TOP NOTCH QUALITY</p> 	<p>NEW! MW-S10-S</p>	<p>MULTIPURPOSE PLIERS, CUTTER, & WIRE STRIPPER. STRIP WIRES FROM 10 TO 20 AWG AND CUT WITH SHEARING KNIFE EDGE. PULL WITH BUILT-IN PLIERS. OVERALL LENGTH IS 5-1/2"</p>	<p>NEW!</p> 	<p>DP-512-B</p>	<p>DIAGONAL PLIERS TO CUT HEAVY GAGE COPPER WIRE UP TO 12 AWG. OVERALL LENGTH OF PLIERS IS 5". BLUNT CUT.</p>
<p>NEW!</p> 	<p>RS-828-KB</p>	<p>ROUND CABLE STRIPPER. STRAIGHT & RING-CUT CABLE FROM 5/16" TO 1". STRIP JACKETED CABLES, PVC, RUBBER, ETC.</p>	<p>NEW!</p> 	<p>ML-NP6-T7</p>	<p>PROFESSIONAL NEEDLE NOSE PLIERS. LENGTH OF JAWS 1-1/4". OVERALL LENGTH OF PLIERS IS 5-1/2". HEAVY DUTY CONTOURED HANDLES.</p>

A SMALL COMPANY WITH BIG IDEAS®



392 PACIFIC STREET, STAMFORD, CT 06902
 PHONE (203) 324-0067 ☆ FAX (203) 324-7844 ☆ E-Mail: info@SeatekCo.com
 Web Site: WWW.SeatekCo.com

